

# PS4000 C-SJ5-25

## Solar Submersible Pump System for 4" wells

### System Overview

Head	max. 140 m
Flow rate	max. 7.0 m³/h

PS DataModule – Integrated Data Logger and advanced pump management features. Allows for simple system configuration, real-time and stored data plus provides Bluetooth communication to PumpScanner Android™ App and PS Communicator.\*

### Technical Data

#### Controller PS4000

- Control inputs for dry running protection, remote control etc.
- Protected against reverse polarity, overload and overtemperature
- Integrated MPPT (Maximum Power Point Tracking)

Power	max. 4.0 kW
Input voltage	max. 375 V
Optimum Vmp**	> 238 V
Motor current	max. 15 A
Efficiency	max. 98 %
Ambient temp.	-30...50 °C
Enclosure class	IP65

#### Motor ECDRIVE 4000-C

- Maintenance-free brushless DC motor
- Water filled
- Premium materials, stainless steel: AISI 304/316
- No electronics in the motor

Rated power	4.0 kW
Efficiency	max. 92 %
Motor speed	900...3,300 rpm
Insulation class	F
Enclosure class	IP68
Submersion	max. 150 m

#### Pump End PE C-SJ5-25

- Non-return valve
- Premium materials, stainless steel: AISI 304
- Optional: dry running protection
- Centrifugal pump

#### Pump Unit PU4000 C-SJ5-25 (Motor, Pump End)

Borehole diameter	min. 4,0 in
Water temperature	max. 50 °C



### Standards



2006/42/EC, 2004/108/EC, 2006/95/EC



Type Approved  
Safety  
Regular Production  
Surveillance  
www.tuv.com  
ID 2000000000

IEC/EN 61010-1:2010, IEC 62103:2003, IEC/EN 60034-1:2010,  
IEC/EN 60335-2-41:2003+A1+A2,  
IEC/EN 60335-1:2012, EN 62233:2008  
IEC/EN 61000-6-4:2007+A1, IEC/EN 61000-6-2:2005

IEC/EN 61702:1995, IEC/EN 62253 Ed.1

The logos shown reflect the approvals that have been granted for this product family. Products are ordered and supplied with the approvals specific to the market requirements.

\* PS DataModule is included in all PSk2 controllers and any PS controllers with –D in their description. –D variants should be ordered if there is a potential need to use the PS DataModule features in the future as this is not a retrofit option.

\*\*Vmp: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature




# PS4000 C-SJ5-25

## Solar Submersible Pump System for 4" wells

### Pump Chart


V<sub>mp</sub>\* > 238 V



### Dimensions and Weights


#### Controller

H = 595 mm  
H2 = 563 mm  
W1 = 178 mm  
W2 = 156 mm  
W3 = 116 mm  
D = 165 mm  
D1 = 150 mm



#### Pump Unit

A = 941 mm  
B = 245 mm  
C = 696 mm  
D = 96 mm  
E = 98 mm  
S = 1.5 in



	Net weight
Controller	9.0 kg
Pump Unit	18 kg
Motor	10 kg
Pump End	8.0 kg

\*V<sub>mp</sub>: MPP-voltage under Standard Test Conditions (STC): 1000 W/m² solar irradiance, 25 °C cell temperature

